



SHORT THROW PROJECTOR

	
Model	PT-TX430
Price	₱53,750.00
Projector Type	LCD Technology
Panel Size (Diagonal)	16.0 mm (0.63")
Display Method	Transparent LCD Panel
Drive Method	Active Matrix Method
Brightness	3,800 Lumens
Native Resolution	XGA (1024 x 768)
Contrast Ratio	16,000:1
Screen Size (Diagonal)	1.27–2.54 m (50"–100")
Aspect Ratio	4:3
Center-to-corner uniformity ²	85 %
Lens	Fixed Zoom, Manual Focus Lens, F = 1.8, f = 6.08 mm, Throw Ratio: 0.46:1
Vertical Keystone	±15° (Auto, Manual)
Horizontal Keystone	±15° (Manual)
Terminals	HDMI 19p, VGA x3 (In x2/Out), Video in (Pin jack x1), Audio-In x2 (M3 x1/Pin jack x2), Audio-Out (M3 x1 [variable]), LAN, RS232C, USB Type-A (for Memory Viewer Light/Wireless Module [DC 5V/500 mA Max.], USB Type-B (for USB Display)
Lamp Replacement Cycle (Hours)	Normal: 10,000 Eco: 20,000 Quiet: 10,000
Filter Replacement Cycle (Hours)	Normal: 5,000 Eco: 6,000 Quiet: 10,000
Built-in Speaker	10W (Mono)
Cabinet Materials	Molded Plastic (PC)
Operation Noise	Normal: 39 dB, Eco: 35 dB, Quiet: 30 dB
Dimensions (W x H x D)	13" x 5" x 12"
Weight	Approx. 3.9 kg.
Power Consumption	300W (6W with Standby mode set to Normal, 0.5W with Standby mode set to Eco)
Power Supply	AC 100-240 V, 50 Hz/60 Hz
Warranty	3 years on parts and service except bulb and lens. 6 months or 500 hours on bulb. Whichever comes first.